



Slicer Selection Guide

2153 Dryden Rd., Dayton, OH 45439 | 937-299-5493 | 800-347-5423 | Fax: 937-299-4147 | www.globefoodequip.com

Model No.	Slicing Volume	Precision Slicing Index	Manual (Slice to Order)	Auto (Bulk Slicing)	Cheese Slicing	Drive Type	Construction	Motor	Blade (Diameter)	Max. Slice Thickness	Cutting Capacity		
											D (Diameter)	W (Width)	H (Height)
NEW! Globe® S-Series Heavy Duty Premium Slicers													
S13 & SG13	All Day	●	✓		●	Belt	Anodized Aluminum	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	8" (20.3cm)	11" (27.9cm)	13.75" (34.9cm)
S13A & SG13A	All Day	●	✓	✓	●	Belt	Anodized Aluminum	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	8" (20.3cm)	11" (27.9cm)	13.75" (34.9cm)
S13-F	All Day	●	✓		●	Belt	Anodized Aluminum	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	8" (20.3cm)	11" (27.9cm)	13.75" (34.9cm)
S13A-F	All Day	●	✓	✓	●	Belt	Anodized Aluminum	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	8" (20.3cm)	11" (27.9cm)	13.75" (34.9cm)
Globe® N-Series Heavy Duty Premium Slicers													
3600N & 4600N	All Day	●	✓		●	Gear	Stainless Steel	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	9" (22.86cm)	11.6" (29.46cm)
3850N (2 Speed)	All Day	●	✓	✓	●	Gear	Stainless Steel	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	9" (22.86cm)	11.6" (29.46cm)
3600NF & 3975NF Frozen	All Day	●	Both ✓	3975NF only ✓	●	Gear	Stainless Steel	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	9" (22.86cm)	11.6" (29.46cm)
3975N - 4975N (9 Speed)	All Day	●	✓	✓	●	Gear	Stainless Steel	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	9" (22.86cm)	11.6" (29.46cm)
Globe® G-Series Medium Duty Slicers													
GC512	4 Hours	◐	✓		◐	Gear	Aluminum/ Stainless Steel	1/3 HP	12" (30.48cm)	7/8" (2.22cm)	7.5" (19.50cm)	10" (25.40cm)	8.75" (22.23cm)
G14 G14-Q	3 Hours	◐	✓		◐	Belt	Aluminum	1/2 HP	14" (35.56cm)	9/16" (1.43cm)	9.75" (24.8cm)	11.5" (29.2cm)	10.125" (25.7cm)
G12A	2.5 Hours	◐	✓	✓	◐	Belt	Aluminum	1/2 HP	12" (30.48cm)	1/2" (1.27cm)	8.25" (21cm)	10" (25.4cm)	8.75" (22.2)
G12 G12-Q	2.5 Hours	◐	✓		◐	Belt	Aluminum	1/2 HP	12" (30.48cm)	9/16" (1.43cm)	8.25" (21cm)	10" (25.4cm)	8.75" (22.2)
G10	1 Hour	◐	✓		◐	Belt	Aluminum	1/3 HP	10" (25.40cm)	9/16" (1.43cm)	7.25" (18.4cm)	9.5" (24.1cm)	7.375" (18.7cm)
Chefmate® by Globe C-Series Economy and E-Series Light Duty Slicers													
C12	1 Hour	◐	✓		◐	Belt	Aluminum	1/3 HP	12" (30.48cm)	9/16" (1.43cm)	8" (20.32cm)	9.75" (24.77cm)	8.62" (21.89cm)
C10	30 Minutes	◐	✓		○	Belt	Aluminum	1/4 HP	10" (25.40cm)	9/16" (1.43cm)	6.87" (17.45cm)	8.62" (21.89cm)	7.25" (18.42cm)
C9	< 30 Min.	◐	✓		○	Belt	Aluminum	1/4 HP	9" (22.86cm)	9/16" (1.43cm)	6.25" (15.88cm)	7.25" (18.42cm)	6.5" (16.51cm)



GLOBE FOOD EQUIPMENT CO.

Guía de la Selección de la Máquinas de Cortar

2153 Dryden Rd., Dayton, OH 45439 | 937-299-5493 | 800-347-5423 | Fax: 937-299-4147 | www.globefoodequip.com

Núm. de Modelo	Volumen de rebanado	Índice de precisión al rebanar	Manual (Rebanado a pedido)	Automático (Rebanado al granar)	El Rebanar del queso	Tipo de Transmisión	Construcción	Motor	Lámina (Diámetro)	Grueso Máximo de la rebanada	Capacidad del Corte		
											D (Diámetro)	W (Anchura)	H (Altura)
NUEVO! Globe® S-Series Heavy Duty Premium Slicers													
S13 & SG13	Todo el día	●	✓		●	Correa	El aluminio anodizado	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	8" (20.3cm)	11" (27.9cm)	13.75" (34.9cm)
S13A & SG13A	Todo el día	●	✓	✓	●	Correa	El aluminio anodizado	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	8" (20.3cm)	11" (27.9cm)	13.75" (34.9cm)
S13-F	Todo el día	●	✓		●	Correa	El aluminio anodizado	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	8" (20.3cm)	11" (27.9cm)	13.75" (34.9cm)
S13A-F	Todo el día	●	✓	✓	●	Correa	El aluminio anodizado	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	8" (20.3cm)	11" (27.9cm)	13.75" (34.9cm)
Globe® N-Series Heavy Duty Premium Slicers													
3600N & 4600N	Todo el día	●	✓		●	Engranaje	Acero Inoxidable	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	9" (22.86cm)	11.6" (29.46cm)
3850N (2 Speed)	Todo el día	●	✓	✓	●	Engranaje	Acero Inoxidable	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	9" (22.86cm)	11.6" (29.46cm)
3600NF & 3975NF Frozen	Todo el día	●	✓	3975NF sólo ✓	●	Engranaje	Acero Inoxidable	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	9" (22.86cm)	11.6" (29.46cm)
3975N - 4975N (9 Speed)	Todo el día	●	✓	✓	●	Engranaje	Acero Inoxidable	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	9" (22.86cm)	11.6" (29.46cm)
Globe® G-Series Medium Duty Slicers													
GC512	4 horas	●	✓		●	Engranaje	Aluminio/Acero Inoxidable	1/3 HP	12" (30.48cm)	7/8" (2.22cm)	7.5" (19.50cm)	10" (25.40cm)	8.75" (22.23cm)
G14 G14-Q	3 horas	●	✓		●	Correa	Aluminio	1/2 HP	14" (35.56cm)	9/16" (1.43cm)	9.75" (24.8cm)	11.5" (29.2cm)	10.125" (25.7cm)
G12A	2.5 horas	●	✓	✓	●	Correa	Aluminio	1/2 HP	12" (30.48cm)	1/2" (1.27cm)	8.25" (21cm)	10" (25.4cm)	8.75" (22.2)
G12 G12-Q	2.5 horas	●	✓		●	Correa	Aluminio	1/2 HP	12" (30.48cm)	9/16" (1.43cm)	8.25" (21cm)	10" (25.4cm)	8.75" (22.2)
G10	1 hora	●	✓		●	Correa	Aluminio	1/3 HP	10" (25.40cm)	9/16" (1.43cm)	7.25" (18.4cm)	9.5" (24.1cm)	7.375" (18.7cm)
Chefmate® by Globe C-Series Economy and E-Series Light Duty Slicers													
C12	1 hora	●	✓		●	Correa	Aluminio	1/3 HP	12" (30.48cm)	9/16" (1.43cm)	8" (20.32cm)	9.75" (24.77cm)	8.62" (21.89cm)
C10	30 minuto	●	✓		○	Correa	Aluminio	1/4 HP	10" (25.40cm)	9/16" (1.43cm)	6.87" (17.45cm)	8.62" (21.89cm)	7.25" (18.42cm)
C9	< 30 min.	●	✓		○	Correa	Aluminio	1/4 HP	9" (22.86cm)	9/16" (1.43cm)	6.25" (15.88cm)	7.25" (18.42cm)	6.5" (16.51cm)